

BlackBrite – SpecData Sheet

Product Standards

Standard Gauges & Widths	
0.0250" x 48.5"	0.6mm x 1232mm
Additional gauges / widths available upon request. Minimum order quantities apply.	
Aluminum Standards	
Alloy:	5657
Material Finish:	One Side Bright
Temper:	H25
UTS:	21-28 KSI
UYS:	15-25 KSI
Elongation:	2%
Bend Radii:	Gauge range specific – information available upon request.
Anodize Standards	
Gloss:	N/A
Optics:	N/A
Anodize Finish:	Brightened
Film Min/Max:	0.300 – 0.425 mils
Standard Film:	0.350 mils
Color:	L = 23.0 +/- 3.0 A = 0.0 +/- 1.5 B = -1.0 +/- 2.0
2 Sided Product:	No
UV Stable:	No
Ordering Specifics	
Available as Tolling:	Yes

Additional Product Information

Availability

Standard anodized lead time = two weeks.

Warranty

Warranties are job specific – please complete the Warranty Application Form available online at www.lorin.com.

Surface Protection

Lorin recommends that surface protection be applied to all bright sheet products.

Lorin Standards

Certification

- Chemical Composition – Standard
- Mechanical Composition – Standard
- Slit / Sheeted Certification – Upon Request

Packaging Standards

- Coil = Eye Vertical
- Sheet = Full Wooden Box

Shipping Quantity Tolerances

- +/- 10% Order Line Quantity