

## ClearMatt Micro – SpecData Sheet

### Product Standards

Standard Gauges & Widths	
0.0240" x 48.5"	0.6mm x 1232mm
Additional gauges / widths available upon request. Minimum order quantities apply.	
Aluminum Standards	
Alloy:	5205
Material Finish:	MicroMatt
Temper:	H34
UTS:	20-26 KSI
UYS:	16 min KSI
Elongation:	3%
Bend Radii:	Gauge range specific – information available upon request.
Anodize Standards	
Gloss:	15 +/- 5
Optics:	N/A
Anodize Finish:	Etched
Film Min/Max:	0.000-0.999
Anodic Film(s):	0.125 mils
Color:	L = N/A A = N/A B = N/A
2 Sided Product:	No
UV Stable:	Yes
Ordering Specifics	
Available as Tolling:	No

### Additional Product Information

#### Availability

Standard anodized lead time = two weeks.

#### Warranty

Warranties are job specific – please complete the Warranty Application Form available online at [www.lorin.com](http://www.lorin.com).

#### Surface Protection

Lorin recommends but does not require surface protection be applied to all bright sheet products.

### Lorin Standards

#### Certification

- Chemical Composition – Standard
- Mechanical Composition – Standard
- Slit / Sheeted Certification – Upon Request

#### Packaging Standards

- Coil = Eye Vertical
- Sheet = Full Wooden Box

#### Shipping Quantity Tolerances

- +/- 10% Order Line Quantity