

Lamina – NaturalMatt 90 Gloss SpecData Sheet

Product Standards

Standard Gauges & Widths	
0.005" x 50.0"	0.1mm x 1270mm
Additional gauges / widths available upon request. Minimum order quantities apply.	
Aluminum Standards	
Alloy:	5205
Material Finish:	Mill Finish
Temper:	H18
UTS:	29 KSI
UYS:	28 KSI
Elongation:	4%
Bend Radii:	Gauge range specific – information available upon request.
Anodize Standards	
Gloss:	90 +/- 10
Optics:	N/A
Anodize Finish:	Etched
Film Min/Max:	0.000-0.999
Anodic Film(s):	0.175
Color:	L = N/A A = N/A B = N/A
2 Sided Product:	No
UV Stable:	Yes
Ordering Specifics	
Available as Tolling:	No

Additional Product Information

Availability

Standard anodize lead time = two weeks.

Warranty

Warranties are job specific – please complete the Warranty Application Form available online at www.lorin.com.

Surface Protection

Lorin recommends surface protection be applied to all bright sheet products.

Visual Standards

Because of its thin gauge, slight indentations may occur on the metal surface of the Lamina product. These indentations are easily removed within a high pressure laminate process.

Material Inspection

Lorin utilizes a standard visual review of our finished products from 5 feet or 1.5 meters back from the sheet looking straight at the material hanging from a vertical surface. Material is viewed for consistency from edge to edge.

Lorin Standards

Certification

- Chemical Composition – Standard
- Mechanical Composition – Standard
- Slit / Sheeted Certification – Upon Request

Packaging Standards

- Coil = Eye Vertical
- Sheet = Full Wooden Box

Shipping Quantity Tolerances

- +/- 10% Order Line Quantity