


# PERFORATED ANODIZED ALUMINUM


The following perforated patterns are available in coil by Lorin \*



0.250 0.375 40%

**Pattern 121**


Gauge: 0.020"-0.080" (0.5mm-2.0mm)  
Max Width: 60" (1524mm)



0.250 0.4375 30%

**Pattern 122**


Gauge: 0.050"-0.080" (1.3mm-2.0mm)  
Max Width: 60" (1524mm)



0.250 0.500 23%

**Pattern 123**


Gauge: 0.020"-0.080" (0.5mm-2.0mm)  
Max Width: 48" (1219mm)



0.375 0.50 51%

**Pattern 124**


Gauge: 0.016"-0.080" (0.4mm-2.0mm)  
Max Width: 60" (1524mm)



0.375 0.5625 40%

**Pattern 125**


Gauge: 0.020"-0.080" (0.5mm-2.0mm)  
Max Width: 60" (1524mm)



0.4375 0.625 44%

**Pattern 127**

Gauge: 0.020"-0.080" (0.5mm-2.0mm)  
Max Width: 60" (1524mm)



0.500 0.6875 48%

**Pattern 128**

Gauge: 0.020"-0.080" (0.5mm-2.0mm)  
Max Width: 60" (1524mm)

**Add  
some  
excitement  
to your  
design  
with  
COLOR**

**Round Holes, Staggered Patterns**  
*Pictures are shown at 50% Scale*

Key: Hole Size Centers Open Area

\* There may be some limitations for these patterns depending upon gauge and width requirements.

800.654.1159

Int'l 231.722.1631

[www.lorin.com](http://www.lorin.com)

**LORIN**

LPAED1804R1